

STRUCTURAL • CORROSION-RESISTANT

CTX

CONSTRUCTION LAG SCREW



Star
Drive



Round
Washer
Head

ACQ
COMPATIBLE

- Bronze Coating
- Star Drive
- Type 17 Point



TER 2104-04

Scan for Tech Data



Compatible with treated lumber, but areas within one mile of saltwater, near swimming pools, exposure to corrosive chemicals, or other areas where corrosion is more likely to occur, such as livestock confinement, use the proper size, grade and type of Big Timber Stainless Steel Fasteners. *Stainless available as SCTX.*



BENEFITS & FEATURES:

- Heat-treated hardened steel for high tensile strength and high shear strength
- Triple Layer ACQ Compatible Bronze Coating for Exterior or Interior use
- Built-in washer head for increased pull through strength
- Under-head cutting nibs to aid in self countersinking
- Aggressive knurl enlarges hole to reduce splitting and drag to help draw lumber together
- V-Cut notches on threads to cut fibers for easier insertion at lower torque
- Type 17 tip for faster precise starts which eliminate "walking" and provides easier insertion without pre-drilling
- Aggressive Thread for great withdrawal strength
- Structural Lag Screw backed by certified independent testing (TER 1907-01) (Acceptable alternative to galvanized lag screws)
- International Building Code and International Residential Code Compliant

COMMON USES INCLUDE:

- Log Construction
- Timber Frames
- Laminated Beams
- Girders
- Ledger Boards
- Stair Rails
- Deck Posts
- Fencing
- SIP Panels
- Pole Barns

NOTE: Always follow lumber manufacturer's recommendations.

Available Sizes • #14 x 1-1/2" to #17 x 16"

AVAILABLE DRIVE
AND SHANK SIZES:

T25 ▶ (#14 / 0.168 IN)

T30 ▶ (#15 / 0.202 IN)

T40 ▶ (#17 / 0.226 IN)

DIAMETER / DRIVE	LENGTH	AVERAGE ULTIMATE LOAD
0.531" / T25	1 ½ - 3"	930 lbf (Shear 725 lbf)
0.620" / T30	3 - 6"	1,475 lbf (Shear 1,020 lbf)
0.675" / T40	4 - 16"	1,850 lbf (Shear 1,240 lbf)



TO LEARN MORE ABOUT OUR PRODUCTS GO TO

▶ **BigTimberFasteners.ca**