## **EXTERIOR CORROSION-RESISTANT**

## COMPOSITE DECK SCREW





Cylinder

COMPATIBLE

- Exterior Coating
- Dual Thread
- Type 17 Point

Scan for Tech Data





Compatible with treated lumber, but areas within one mile of saltwater, near swimming pools, exposure to corrosive chemicals, or other areas where corrosion is more likely to occur, such as livestock confinement, use the proper size, grade and type of Big Timber Stainless Steel Fasteners. Big Timber Stainless Steel Fasteners should be considered if available. CD is not available in stainless.



## **BENEFITS & FEATURES:**

- · Heat-treated hardened steel for high tensile strength and high shear strength
- 1200 HR ACQ compatible coating for exterior or interior use
- · Offers a clean finish look in all types of deck boards to include:
  - Cap-stock decking
  - PVC decking
  - Composite decking
- Dual under-head cutting nibs to aid in self countersinking
- 10° tapered head design and the reverse threads to prevent mushrooming or "volcanoing"
- Dual-thread (fine/coarse) cuts through fibrous materials with ease reducing torque - Maximized holding power
- Type-17 tip for faster precise starts which eliminate "walking"
  - Provides easier insertion without pre-drilling
- · Available in 2 common composite deck board colours:
  - Cape Cod Gray
  - Walnut

## **COMMON USES INCLUDE:**

- · Composite Deck Board Installation
- · Composite Fascia Board Installation
- · Composite Railings

- · Composite Trim Boards
- Wood Siding

NOTE: Always follow lumber manufacturer's recommendations.

**Available Sizes:** #10 x 2-3/4"

> **AVAILABLE DRIVE AND SHANK SIZES:**

T20 (#10 / 0.128 IN)

DIAMETER / DRIVE	LENGTH	
0.128"/ T20	2¾"	

